

DIGITAL PRO DJ-PAX4 degreen

UHF License-Free Transceiver

A Simple, Reliable yet Affordable Dual Mode dPMR446 Transceiver

Digital / Analogue Dual mode & User-friendly operability

The DJ-PAX4 is a digital/analog dual mode transceiver compatible with dPMR™ 446 operation. Eliminating a display and keypad operations, DJ-PAX4 makes it ideal for simple business communications.

Long lasting battery life & Fast charge

A large capacity waterproof battery pack, EBP-101 (1800mAh typ.) provides 14 hours of operating time. The supplied charger charges an empty battery pack in 4 hours.

Clear & Loud Audio

A powerful 1W audio output and an AMBE+2 ™ vocoder delivers high quality, noise-free and crisp sounds.

Safety and Security features

Digital voice scrambler, Lone worker and Emergency call features provide safer and secure communications.

Ingress Protection 67 and MIL-810G Shock / Vibration tested

A compact yet rugged construction, DJ-PAX4 is rated IP67 protection against dusts and water. DJ-PAX4 has also been tested to comply MIL-STD 810G shock and vibration Standards.

(Voids IP67 when an external microphone is connected.)

Up to 80 programmable channels in 5 groups

72 Channels are preprogrammed with frequencies, CTCSS, DCS squelch tones or digital ID as default, leaving 8 empty channels for user customization.

(24 analogue channels and 8 empty channels in 2 groups, 56 digital channels in 3 groups, 16ch per group)







Convenient Features

- Voice Announcement
- Programmable Side & Top keys
- •Built-in VOX (A third party, compatible earphone-microphone required.)
- PC Programming
- Auto Power Off
- ·Busy Channel Scan
- ·Priority Scan
- •CTCSS/DCS Encode & Decode (Analogue mode)
- ·255 Common IDs
- ·Time-out Timer
- ·Battery Saver
- ·Busy Channel Lockout



Standard Accessories



Specifications

GENERAL			
Frequency Range	446.0 - 446.2 MHz		
Channel Capacity	80ch (16ch x 5 groups)		
Channel Spacing Analogue	12.5 kHz		
Digital	6 . 25 kHz		
Operating Voltage	7.4V DC±20%		
Detter life *	Battery Save: OFF	Battery Save: ON	
Battery Life *	14hours	19hours	
Frequency Stability	±2.5 ppm		
Dimensions (WxHxD w/o projection)	102x59x38mm (with EBP-101) Antenna length 140mm		
Weight (With EBP-101)	238g		
RF Power Output	500 mW		
Audio Output	1W (10%)		
Analogue (12.5kHz)	8K50F3E		
Modulation Digital (6.25kHz)	4K00F1E		
Operating temperature range	-20~+60°C(Operating) / +5~+40°C(Charging)		

^{*} Based upon 5% transmit/ 5% receive/ 90% standby (standard duty cycle) Specifications subject to change without notice or obligation.

Standard Accessories	(A strap is included)

Antenna	Li-ion Battery Pack	Rapid Charger Stand	AC Adapter	Belt Clip
(Fixed)	EBP-101 Li-ion 7.4V 1800mAh	EDC-219	EDC-221	EBC-51

Standard accessories declared herein are our factory default and may vary at moment of sales depending on the market and Dealers' sales policy.

Options



 PC Interface Cable (ERW-22) Please consult your dealer for utility software before purchase. Alinco releases such software to authorized dealers only.



- Managers & Cashiers
- Kitchen & Wait Staff
- Parking Attendants & Cloakroom



- Front Desk & Concierge
- Maintenance & Cleaning
- Security



- Factory
- Warehouse
- Office
- Shop



- Public office
- laboratory
- School
- Coaches & Trainers
- Events

Authorized Dealer:



Ruselbergstraße 4 DE- 94469 Deggendorf info@on-radio-shop.de Tel.:+49 (0) 991/981590-36 FAX:+49 (0) 991/981590-37 https://www.on-radio-shop.de Copyright Alinco,Inc., Osaka, Japan. All rights reserved. Although Alinco has designed this brochure to be as accurate and comprehensive as possible, we reserve the right to make changes at any time to our equipment line, optional accessories, specifications, standard accessories, or availability of any such devices we manufacture and distribute. Please note that certain products and accessories may not be available in all countries of distribution therefore consult your Authorized Alinco Dealer for product availability and pricing. Colors of images herein may appear slightly different from actual products due to print.

* Projections are not included in the declared dimension values.

Manufacturer :

ALINCO, INC. Electronics Division Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi,

Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi, Chuo-ku, Osaka 541-0043 Japan Phone: +81-6-7636-2362 Fax: +86-6-6208-3801 http://www.ALINCO.com E-mail: export@alinco.co.ip